

NOTES:

 \forall

- FOIL IS 0.05mm [0.002 INCHES] THICK.
 FOIL IS 99.995% 4N5 PURE INDIUM.
- 3. FOIL IS VACUUM SEALED IN BETWEEN 2 PLASTIC SHEETS FOR SHIPPING AND STORAGE PROTECTION.
- 4. SEE SPECIFICATION SHEET FOR MORE INFORMATION.

| TH IS | PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CUSTOM THERMOELECTRIC, LLC. ANY REPRODUCTION IN | | | | | Your Thermoelectric Partner | | | | Custom Thermoelectric, LLC 11941 Industrial Park Road, STE 5 Bishopville, MD 21813 PH 443-926-9135 FX 443-926-9137 temodule@customthermoelectric.com | | |
|----------|---|-----------------------------------|--|-----------------------|---------------------------------|-----------------------------|--------|---------|---------|--|----|--|
| PE | PERMISSION OF CUSTOM THERMOELECTRIC. | | | | | | F | OIL THE | -RM | | FT | |
| I - | | | | | | | | · · | | _ \ V / | | |
| Т | | | UNLESS OTH ETERS = ± 1mm = ± 0.25mm = ± 0.10mm | INCHES X.X X.XX | | | | - | x 0.05m | | | |
| | | MILLIM X X.X X.XX | ETERS = ± 1mm = ± 0.25mm = ± 0.10mm | INCHES X.X X.XX | S = ± 0.1 = ± 0.01 | | | - | | | | |
| A | | MILLIM X X.X X.XX VED | ETERS = ± 1mm = ± 0.25mm = ± 0.10mm | INCHES X.X X.XX | S = ± 0.1 = ± 0.01 | 15 | 0 x 15 | - | x 0.05m | | | |

